



Cracked Earth



Hard Rock




Plymouth Rock



Rosetta Stone



Stonehenge



Forces Collection | Earth Rock*



PRODUCT SPECIFICATIONS

Construction	Tufted Colour Placement
Fibre Type	Stainproof SDX (Solution Dyed Nylon)
Recycled Content	Yes - Colour & Backing Dependent
Use Classification	Heavy Commercial
Pile Height	2.5mm to 6mm (± 0.5mm)
Total Thickness	9mm (± 0.5mm)
Total Mass	4910 g/m ² **
Standard Sizing	50cm x 50cm***
Machine Gauge	1/10"
Stitches / 10cm	36
Fire Index	2 (SANS 10177 - IV)
Colourfastness To:	
(i) Light	7 (ISO 105 - B02)
(ii) Rubbing	(a) Wet 4 - 5 (ISO 105 - X12)
Rubbing	(b) Dry 4 - 5 (ISO 105 - X12)
(iii) Water	4 - 5 (ISO 105 - E01)
Electrostatic Propensity	Less than 2.0 kV (ISO 6356 & EN 1307)
Static Control	Permanent
VOC Tested	Pass

Note: Carpet protector mats are necessary where castor wheels are used. ** Weighted average. *** Also available in 60cm x 60cm, 1m x 50 cm and 1m x 1m NexBac tiles and 30cm x 120cm NexBac plank tiles. As these sizes are not standard, minimum production quantities apply. Please contact your nearest Belgotex Floors representative for more information.

