## **Alexandria**











Construction	Scroll Loop Pile Carpet
Yarn	100% Solution Dyed Nylon
Width	4.0m
Standard Roll Length	35m
Yarn Weight	1460g/m² / 43oz/yd²
Total Weight	2365g/m²
Pile Height	9.0mm
Total Thickness	11.0mm
Machine Gauge	1/5 "
Primary Backing	Woven Polypropylene
Secondary Backing	Action Fleece
<b>Electrical Properties</b>	Antistatic
<b>Electrical Propensity</b>	< 2kV (EN 1815 / ISO 6356)
Fire Rating	CRF 4.8kW/m² (AS/ISO 9239-1)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
Rating	Extra Heavy Duty Residential Heavy Duty Commercial
Stair Rating	Suitable
Warranties	15 Year Residential Warranty 5 Year Commercial Warranty
Installation	All seams must be sealed.  Must be laid in accordance with AS/NZ Installation Standards.
Environmental	CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001 Occupational Health and Safety Management ISO 45001



- $\bullet~$  For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex<sup>®</sup>

A world of perfect choices\_

belgotex.com.au 27/02/2024