

Aqua Elite Floating Floor Underlay is a closed cell, electron beam crosslinked, polyolefin foam with an outer skin and additional PE vapour barrier film. The composite is free of heavy metals, plasticisers and CFC's.

Category	Underlay
Thickness	2.5mm
Width	1.0m
Standard Roll Length	25lm
Compressive Strength @ 25% deflection	109kPa (EN 826)
Compressive Creep @ 10 years, <10% deflection	20kPa (EN 1606)
Thermal Resistance 23°C mean temperature	0.073m²K/W (ASTM C518)
Water Vapour Diffusion Resistance, SD	>75m - exceeds EN 16354 requirement
Water Absorption	<1% v/v (Internal)
Installation	Integrated peel and stick. Must be properly installed according to the installation instructions.
Environmental	Occupational Health & Safety Management ISO 45001 Environmental Management ISO 14001 Quality Management ISO 9001

- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.