

Aqua



Construction	Tufted Level Cut Loop Pile Carpet
Yarn	100% Nylon
Width	4.0m
Pattern Repeat	W 392cm x L 172cm
Yarn Weight	1240g/m ²
Total Weight	2285g/m ²
Pile Height	5.8mm
Total Thickness	8.7mm
Machine Gauge	1/10th
Backing	Action Back
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV
Fire Rating	Cfl-s1 (EN 13501)
VOC Rating	A+ (AGBB protocol and GUT label)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	ΔLw 28dB (ISO 140-8)
Acoustic Absorption	α _w 0.25 (ISO 11654)
Underfloor Heating	Suitable
Luxury Class	LC4
Rating	Heavy Duty Residential Medium Duty Commercial
Stair Rating	Suitable
Warranties	15 Year Residential Warranty 5 Year Commercial Warranty
Installation	All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	GUT Label LEED® Low VOC 100% Green Electricity Environmental Management ISO 14001 Quality Management ISO 9001



- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A world of
perfect choices_