## BJELIN Woodura S



| Category                                 | European Hardened Timber  |
|--|---|
| Туре                                     | 100% Real Wood - Oak  |
| Plank Size                               | 151mm x 1170mm  |
| Planks per Carton                        | 9pcs / 1.59m²   |
| Weight per Carton                        | 14.34kg   |
| Thickness                                | 9.2mm   |
| Top Layer Thickness                      | 0.6mm   |
| Surface Finishing                        | Pro Matt Lacquer  |
| Core                                     | Ultra HDF   |
| Locking System                           | Välinge 5G Dry  |
| Slip Resistance                          | P3 (AS 4586-2013 Appendix A)  |
| Thermal Resistance - plank only          | 0.075 m <sup>2</sup> K/W (EN 12667)   |
| Thermal Resistance - Aqua Elite underlay | 0.148 m <sup>2</sup> K/W (EN 12667)   |
| Thickness Swelling                       | <10% (EN 14354)   |
| Fire Rating                              | Cfl-s1, CRF ≥ 4.5 kW/m² (EN 13501-1, ISO 9239-1)  |
| Indoor Air Quality                       | A+ Emissions / Indoor Air Comfort Gold®   |
| Formaldehyde Emissions                   | <0.005 ppm, E1 (EN 717-1)   |
| Wear Resistance                          | >6000 cycles (EN 14354)   |
| Impact Resistance                        | EC3 (EN 14354)  |
| Underfloor Heating                       | Suitable - Maximum Temperature 27°C   |
| Classification                           | Class 23 Domestic Heavy<br>Class 33 Commercial Heavy  |
| Stair Rating                             | Suitable  |
| Warranties                               | 35 Year Residential Warranty<br>15 Year Moisture Protection (Kitchen, Laundry, Toilet)<br>Commercial on Request   |
| Installation                             | Must be properly installed according to the installation instructions.  |
| Environmental                            | Forest Stewardship Council (FSC) Nordic Swan Ecolabel Certified GREENGUARD Gold Certified Environmental Product Declaration Quality Management ISO 9001 |
|  |   |









- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Rubber-based materials should not be left in contact with the floor for prolonged periods as they may cause tattooing or permanent staining on the lacquered surface. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.

## Belgotex<sup>®</sup>

A world of perfect choices\_

belgotex.com.au 19/05/2025