

Boundary Rise



Construction	Precision Loop Pile Carpet
Yarn	100% New Zealand Wool
Yarn Specification	Multi-ply twisted, stock dyed
Width	3.66m
Standard Roll Length	30m
Yarn Weight	1350g/m ² / 40oz/yd ²
Pile Height	7.0mm
Total Thickness	10.0mm
Machine Gauge	1/4
Primary Backing	Polypropylene
Secondary Backing	Jute / Hessian
Fire Rating	CRF 5.5kW/m ² (AS ISO 9239.1)
Insect Resistance	Resistant to attacks by wool destroying insects (TWC TM 27)
Electrical Properties	Antistatic
Indoor Air Quality	Low VOC Emissions
Underfloor Heating	Suitable
Rating	Extra Heavy Duty Residential Medium Duty Commercial
Stair Rating	Suitable
Warranties	15 Year Residential Warranty 5 Year Commercial Warranty
Installation	All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Responsible Wool Environmental Management ISO 14001

- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A world of
perfect choices_