



| | |
|-----------------------------------|---|
| Construction | Structured Loop Pile Carpet |
| Yarn | 100% Regenerated Econyl Solution Dyed Nylon |
| Width | 4.0m |
| Pattern Repeat | W 396cm x L 732cm |
| Yarn Weight | 1050g/m ² |
| Total Weight | 2610g/m ² |
| Pile Height | 4.3mm |
| Total Thickness | 9.0mm |
| Machine Gauge | 1/10th |
| Backing | Action Back |
| Electrical Properties | Antistatic |
| Electrical Propensity | ≤ 2kV |
| Fire Rating | CRF 9.8kW/m ² (ISO 9239-1) |
| VOC Rating | A+ (AGBB protocol and GUT label) |
| Anti-allergenic Properties | Will not shed or pill. Resistant to mould & mildew. |
| Acoustic Insulation | ΔLw 27dB (ISO 140-8) |
| Acoustic Absorbtion | α _w 0.25 (ISO 11654) |
| Underfloor Heating | Suitable |
| Luxury Class | LC3 |
| Rating | Heavy Duty Commercial |
| Stair Rating | Suitable |
| Warranties | 15 Year Residential Warranty 5 Year Commercial Warranty |
| Installation | All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. |
| Environmental | GUT Label LEED® BREEAM Low VOC Recycled Fibre 100% Green Electricity Environmental Product Declaration Environmental Management ISO 14001 Quality Management ISO 9001 |



- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.