

Davenport



Construction	Luxury Vinyl Tile
Plank Size	1219.2mm x 184.2mm
Tiles per Carton	15pcs / 3.37m ²
Wearlayer Thickness	0.55mm
Total Thickness	3.0mm
Backing	Dry Back
Slip Resistance	P3 (EN 13893)
Fire Rating	CRF 10.5kW/m ² (AS/ISO 9239.1)
Dimensional Stability	≤0.12% (EN 434)
Curling	≤1.2mm (EN 434)
Residual Indentation	≤0.1mm (EN 434)
Colour Fastness	6 (ISO 105-B02)
Formaldehyde Group	E1 (EN 717-1)
Indoor Air Quality	FloorScore®
Underfloor Heating	Suitable, max 27°C (EN 12524)
Wet Areas	Suitable (ISO 4760:2022)
Resistance to Staining	Excellent (EN 423)
Abrasion Resistance	Group T (EN 660)
Classification	Heavy Duty Residential Heavy Duty Commercial
Stair Rating	Suitable
Warranty	20 Year Residential Warranty 10 Year Commercial Warranty
Installation	Must be laid in accordance with AS 1884-2012 Installation Standards.
Environmental	Phthalate Free ISO 9001, ISO 14001



- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Rubber Migration: Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.

Belgotex®

A world of perfect choices_