

Grid



Construction	Patterned Tufted Loop Pile Carpet Tile
Yarn	100% Stainproof SDX (Solution Dyed Nylon)
Size	500mm x 500mm
Pile Weight	475g/m ²
Tiles per Carton	20pcs / 5.0m ²
Pile Height	2.0mm
Total Thickness	5.0mm
Machine Gauge	1/10th
Backing	Flexbac
Electrical Properties	Antistatic
Electrical Propensity	< 2kV (ISO 6356 & EN 1307)
Fire Rating	CRF 9.1kW/m ² (BSEN 13238:2010)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	28dB (EN ISO 10140)
Acoustic Absorption	α_w 0.30 (ISO 354)
Underfloor Heating	Suitable
VOC Rating	Pass (GBCSA/GLP Criteria)
Classification	Heavy Duty Commercial
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Installation	Laying recommendation: Quarter Turn. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Greenstar Low VOC, solution dying uses no water, Eco-Wash™ Treatment Occupational Health and Safety Management ISO 45001 Environmental Management ISO 14001 Quality Management ISO 9001



- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ± 3 mm, Pile Weight $\pm 5\%$.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A world of perfect choices_