

Lake



Construction	Structured Loop Pile Carpet Tile
Yarn	100% Regenerated Econyl Nylon
Size	500mm x 500mm
Tiles per Carton	20pcs / 5.0m ²
Pile Weight	770g/m ²
Total Weight	4365g/m ²
Pile Height	3.4mm
Total Thickness	6.8mm
Machine Gauge	1/12th
Backing	Bitumen
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV
Fire Rating	Bfl-s1 (EN 13501)
VOC Rating	A+ (AGBB protocol and GUT label)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	ΔLw 25dB (ISO 140-8)
Acoustic Absorbtion	α _w 0.20 (ISO 11654)
Dimensional Stability	<0.20% (EN986)
Therman Insulation	<0.15m ² C°/W
Underfloor Heating	Suitable
Colour Fastness	5-6/8 on Grey Scale (ISO105-B02)
Luxury Class	LC2
Rating	Heavy Duty Commercial
Stair Rating	Suitable
Warranties	5 Year Commercial Warranty
Installation	Laying recommendation: Monolithic or Brick. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	GUT Label LEED® BREEAM GreenStar CRI Green Label Certified Low VOC, Contains recycled fibre Environmental Product Declaration Quality Management ISO 9001 Environmental Management ISO 14001



- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A world of perfect choices_