Monash - Cushion









Construction	Loop Pile
Yarn	100% Solution Dyed Nylon
Size	500mm x 500mm
Pile Weight	550g/m²
Tiles per Carton	16pcs / 4.0m²
Pile Height	3.0mm
Total Thickness	8.0mm
Machine Gauge	1/10th
Primary Backing	Non-woven
Secondary Backing	Cushion Back
Electrical Properties	Antistatic
Electrical Propensity	< 2kV (ISO 6356 & EN 1307)
PVC Fire Rating	CRF 4.6kW/m² (ISO 9239.1-2003)
Dimensional Stability	<0.20% (EN 986)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	ΔLw 23dB (ISO 140-8)
Acoustic Absorption	αω 0.30 (ISO 354)
Underfloor Heating	Suitable
Colour Fastness	5/5 on Grey Scale (AATCC/16)
VOC Rating	Pass (GBCSA/GLP Criteria)
Rating	Heavy Duty Commercial
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Installation	Laying recommendation: Quarter turn or Brick. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	CRI Green Label Certified Low VOC, solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001 Occupational Health and Safety Management ISO 45001



- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex^{*}

A world of perfect choices_

belgotex.com.au 27/02/2024