



Construction	Loop Pile
Yarn	100% Solution Dyed Nylon
Size	500mm x 500mm
Pile Weight	550g/m ²
Tiles per Carton	PVC: 20pcs / 5.0m ² / Cushion Back: 16pcs / 4.0m ²
Pile Height	3.0mm
Total Thickness	6.0mm
Machine Gauge	1/10th
Primary Backing	Non-woven Polyester / Nylon
Secondary Backing	PVC or Cushion Back
Electrical Properties	Antistatic
Electrical Propensity	< 2kV (ISO 6356 & EN 1307)
PVC Fire Rating	CRF 4.4kW/m ² (BSEN 13238:2010)
Dimensional Stability	<0.20% (EN 986)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
Colour Fastness	5/5 on Grey Scale (AATCC/16)
VOC Rating	Pass (GBCSA/GLP Criteria)
Rating	Heavy Duty Commercial
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Installation	Laying recommendation: Quarter turn or Brick. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	CRI Green Label Certified Low VOC, solution dyeing uses no water Environmental Management ISO 14001 Quality Management ISO 9001 Occupational Health and Safety Management ISO 45001



- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.