

# Pompadour



<b>Construction</b>	Tufted Cut Pile Carpet
<b>Yarn</b>	100% Regenerated Econyl Solution Dyed Nylon
<b>Width</b>	4.0m
<b>Pattern Repeat</b>	W 396cm x L 220cm
<b>Yarn Weight</b>	1250g/m <sup>2</sup>
<b>Total Weight</b>	2670g/m <sup>2</sup>
<b>Pile Height</b>	6.3mm
<b>Total Thickness</b>	10.0mm
<b>Machine Gauge</b>	1/10th
<b>Backing</b>	Action Back
<b>Electrical Properties</b>	Antistatic
<b>Electrical Propensity</b>	≤ 2kV
<b>Fire Rating</b>	CRF 8.2kW/m <sup>2</sup> (ISO 9239-1)
<b>VOC Rating</b>	A+ (AGBB protocol and GUT label)
<b>Anti-allergenic Properties</b>	Will not shed or pill. Resistant to mould & mildew.
<b>Acoustic Insulation</b>	ΔLw 30dB (ISO 140-8)
<b>Acoustic Absorbtion</b>	α <sub>w</sub> 0.25 (ISO 11654)
<b>Underfloor Heating</b>	Suitable
<b>Luxury Class</b>	LC4
<b>Rating</b>	Heavy Duty Commercial
<b>Stair Rating</b>	Suitable
<b>Warranties</b>	15 Year Residential Warranty 5 Year Commercial Warranty
<b>Installation</b>	All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.
<b>Environmental</b>	GUT Label LEED® Low VOC Recycled Fibre Environmental Management ISO 14001 Quality Management ISO 9001



- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

# Belgotex®

A world of perfect choices\_