## Relic











Construction	Level Cut Loop Pile Carpet
Yarn	100% Premium Solution Dyed Nylon
Width	4.0m
Pattern Repeat	W 95cm x L 77cm
Yarn Weight	900g/m²
Total Weight	1860g/m²
Pile Height	6.5mm
Total Thickness	9.0mm
Machine Gauge	1/10th
Primary Backing	Woven Polypropylene
Secondary Backing	FusionBac
<b>Electrical Properties</b>	Antistatic
<b>Electrical Propensity</b>	≤ 2kV (EN14041)
Fire Rating	CRF 6.5kW/m² (ISO 9239-1)
VOC Rating	Pass (GBCA/GBCSA criteria)
<b>Anti-allergenic Properties</b>	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	ΔLw 27dB (ISO 140-8)
Acoustic Absorbtion	αω 0.25 (ISO 11654)
Underfloor Heating	Suitable
Luxury Class	LC3 (EN 1307)
Rating	Extra Heavy Duty Residential Medium Duty Commercial
Stair Rating	Suitable
Warranties	15 Year Residential Warranty 5 Year commercial Warranty
Installation	All seams must be sealed.  Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Greentag Cerfitied GreenStar Eco-Wash™ Treatment Low VOC, solution dying uses no water Product Health Declaration™ Occupational Health and Safety Management ISO 45001 Environmental Management ISO 14001 Quality Management ISO 9001





- $\bullet~$  For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

## Belgotex<sup>®</sup>

A world of perfect choices\_

belgotex.com.au 27/02/2024