

Romance



Construction	Tufted Cut Pile Carpet
Yarn	100% Regenerated Econyl Solution Dyed Nylon
Width	4.0m
Pattern Repeat	W 24cm x L 24cm
Yarn Weight	1250g/m ²
Total Weight	2670g/m ²
Pile Height	6.3mm
Total Thickness	10.0mm
Machine Gauge	1/10th
Backing	Action Back
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV
Fire Rating	CRF 8.2kW/m ² (ISO 9239-1)
VOC Rating	A+ (AGBB protocol and GUT label)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Acoustic Insulation	ΔLw 30dB (ISO 140-8)
Acoustic Absorbtion	α _w 0.25 (ISO 11654)
Underfloor Heating	Suitable
Luxury Class	LC4
Rating	Heavy Duty Commercial
Stair Rating	Suitable
Warranties	15 Year Residential Warranty 5 Year Commercial Warranty
Installation	All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	GUT Label LEED® Low VOC Recycled Fibre Environmental Management ISO 14001 Quality Management ISO 9001



- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A world of perfect choices_