Smooth









Construction	Textured Level Loop Pile Carpet Plank
Yarn	100% Stainproof SDX (Solution Dyed Nylon)
Size	1000mm x 250mm
Pile Weight	620g/m²
Tiles per Carton	20pcs / 5.0m ²
Pile Height	7.0mm
Total Thickness	10.0mm
Machine Gauge	1/10th
Backing	Flexbac
Electrical Properties	Antistatic
Electrical Propensity	< 2kV (ISO 6356 & EN 1307)
Fire Rating	CRF 8.4kW/m² (ISO 9239-1)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
VOC Rating	Pass (GBCSA/GLP Criteria)
Classification	Heavy Duty Commercial
Stair Rating	Suitable
Warranty	15 Year Commercial Warranty
Installation	Laying recommendation: Ashlar or Herringbone. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Greenstar Low VOC, solution dying uses no water, Eco-Wash™ Treatment Occupational Health and Safety Management ISO 45001 Environmental Management ISO 14001 Quality Management ISO 9001





- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex[®]

A world of perfect choices_

belgotex.com.au 27/02/2024